

U Match

Cassette



R410A

PARAMETER		UNIT	2 PK	3 PK	4 PK	4.5 PK	5 PK	6 PK
Model	Indoor	-	GUD50T/A-K	GU71T/A-K	GU100T/A-K	GU125T/A-K	GU140T/A-K	GU160T/A-K
	Outdoor	-	GUL50W/A-K	GUL71W/A-K	GUL100W/A-M	GUL125W/A-M	GUL140W/A-M	GUL160W/A-M
Suplai Daya	Tegangan	V~	220 - 240		380 - 415			
	Frekuensi	Hz	50					
	Phase	-	1		3			
Kapasitas Pendingin		Btu/h	16720	24225	35144	40944	48109	51180
Daya Listrik Pendingin		kW	1.6	2.35	3.5	4.15	5.6	5.2
EER		W/W	3.06	3.02	2.94	2.89	2.52	2.88
Sirkulasi Udara		m ³ /h	700	1250	1600		2000	
Unit Indoor	Dimensi (PxLxT)	mm	570 x 570 x 265		840 x 840 x 240		840 x 840 x 290	
Unit Outdoor			761 x 256 x 548	892 x 340 x 698	920 x 370 x 790	940 x 460 x 820		
Indoor Panel			620 x 620 x 47.5		950 x 950 x 52			
Sambungan Pipa	Dimensi Luar Pipa Cairan	Inch	1/4"		3/8"			
	Dimensi Luar Pipa Gas		1/2"		5/8"			



Perawatan Mudah



Inner Groove Copper



Wide Voltage Startup



Self Diagnosis



Quality Motor



Dapat Beroperasi Di Suhu Ekstrem



Outdoor Kuat



Perlindungan Komprehensif