

U Match

Duct



R410A

PARAMETER		UNIT	1 PK	1.5 PK	2 PK	3 PK	4 PK	4.5 PK	5 PK	6 PK
Model	Indoor	-	GU26PS/A-K	GU35PS/A-K	GU50PS/A-K	GU71PS/A-K	GU100PHS/A-K	GU125PHS/A-K	GU140PHS/A-K	GU160PHS/A-K
	Outdoor	-	GUL26W/A-K	GUL35W/A-K	GUL50W/A-K	GUL71W/A-K	GUL100W/A-M	GUL125W/A-M	GUL140W/A-M	GUL160W/A-M
Suplai Daya	Tegangan	V~	220 - 240				380 - 415			
	Frekuensi	Hz	50							
	Phase	-	1				3			
Kapasitas Pendingin		Btu/h	9315	12113	17060	24225	35144	40944	48109	54592
Daya Listrik Pendingin		kW	0.94	1.24	1.6	2.35	3.5	4.25	5.25	5.35
ESP	Rated	Pa	25				37		50	
	Range		0-60			0-80	0-100		0-150	
EER		W/W	2.90	2.86	3.12	3.02	2.94	2.82	2.69	2.99
Sirkulasi Udara		m ³ /h	500	600	650	1250	1650	1700	2200	2600
Unit Indoor	Dimensi (PxLxT)	mm	700 x 450 x 200	700 x 450 x 200	1000 x 450 x 200	1300 x 450 x 220	1000 x 700 x 300		1400 x 700 x 300	
Unit Outdoor	Dimensi (PxLxT)		712 x 256 x 548		761 x 256 x 548	892 x 340 x 698	920 x 370 x 790	940 x 460 x 820		
Sambungan Pipa	Dimensi Luar Pipa Cairan	Inch	1/4"				3/8"			
	Dimensi Luar Pipa Gas		3/8"	1/2"			5/8"			



Perawatan Mudah



High ESP



Inner Groove Copper



Wide Voltage Startup



Self Diagnosis



Quality Motor



Outdoor Kuat



Dapat Beroperasi Di Suhu Ekstrem



Perlindungan Komprehensif