

INVERTER R32

FAST COOLING

F5

HEMAT LISTRIK HINGGA

50%

PARAMETER		UNIT	0.5PK	1PK	1.5PK	2PK	2.5PK
Model		-	GWC-05F5S	GWC-09F5S	GWC-12F5S	GWC-18F5S	GWC-24F5S
Tegangan Min./Maks.		V~	220 - 240				
Kapasitas Pendingin		Btu/h	5000	9000	12100	18000	24000
Kapasitas Pendingin Minimum			1706		1200	4436	6150
Kapasitas Pendingin Maksimum			8018	10918	14330	19963	25250
Daya Masukan Pendingin		W	350	655	1170	1500	1920
Daya Listrik Pendingin Minimum			190	330	320	300	450
Daya Listrik Pendingin Maksimum			630	950	1600	1750	2350
CSPF		-	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
Area Aplikasi		m <sup>2</sup>	5-7	11-13	15-17	23-36	30-34
Unit Indoor	Dimensi (PxLxT)	mm	704 x 185 x 260		779 x 185 x 260	982 x 221 x 311	1081 x 248 x 325
Unit Outdoor	Dimensi (PxLxT)		710 x 293 x 450		732 x 330 x 550		873 x 376 x 555
Sambungan Pipa	Diameter Luar Pipa Cairan	Inch	1/4"				
	Diameter Luar Pipa Gas		3/8"				5/8"



Smart Cleaner



Easy Removal



Power Drop



Mass Air Supply



Fast Cooling



Turbo Function



Peningkat Pintar



Self Diagnosis



Timer



Child Lock



Pembersih Otomatis X-Fan



Ramah Lingkungan



Blue Fin & Gold Fin



Anti Getaran



Quiet Function



4 Perlindungan Keamanan



6 Perlindungan Outdoor Anti Karat



Filter HD



Filter DIY